

## SFS-EUL025.0L

2 Head 5 Litres (EU)

## Build to Weigh- Engineered to Last SINGLE VIBRATOR



<b>Bucket Capacity</b>	5.0 liters
<b>Feeding Hopper volume</b>	48 liters
<b>Weighing Range*</b>	50-2000 grams
<b>Accuracy*</b>	+/- 2~3 grams
<b>Production Output* (Speed)</b>	8-10 bags / minute
<b>Operating Panel</b>	Touchscreen HMI 7 Inches
<b>Power Supply</b>	AC 230V +/- 10%, 50/60 Hz
<b>No of Preset Programs</b>	100
<b>Control System</b>	Embedded
<b>Material Of Construction***</b>	All contact parts SS-304. Body Parts MS Powder coated
<b>Machine Dimensions (L x W x H)</b>	590 x 933 x 1196 mm
<b>Machine Weight**</b>	Approx 81 Kgs
<b>Optional Accessories</b>	Customized Structure, Funnel, Elevator, Belt Sealer
<b>Optional Models</b>	SFS-EUL045.0L SFS-EUL027.0L SFS-EUL047.0L

\*Depends on product shape, bulk density, target weight & feeding conditions etc.

\*\*The machine weight varies depending upon the options selected

\*\*\*Complete SS-304 and SS-316 are available on request

### High-Precision Vibratory Feeding

Controlled vibration delivers a smooth, consistent flow of material for highly accurate weighing.

### Dynamic Feed Rate Adjustment

SmartFill auto adjusts vibration intensity on real time load cell feedback to optimize speed and accuracy.

### Multi-Stage Filling

Fast bulk feed transitions into fine and dribble feed for exact target weight achievement with minimal product giveaway.

### HMI Touchscreen Interface

User-friendly, multilingual interface for recipe management, real-time monitoring, and system control. Supports Various Industry 4.0 protocols for smart factory ecosystems.

### Material Flexibility

Capable of handling a wide variety of products like freeflowing granules, powders, small parts, and fragile items.

### Low Maintenance, Long Lifespan

Solid-state vibratory feeders with minimal moving parts, designed for extended service intervals and reduced downtime.

### Tool-free disassembly

Enabling quick and safe removal of all contact parts without any tools. Designed for daily wash-downs, it ensures fast cleaning, minimizes downtime, and meets the highest hygiene standards.

### Protective Enclosures

Prevent contamination from airborne foreign particles. Engineered for food-safe environments, it ensures product purity and compliance with hygiene standards.

